



DELTA-H MOBILE

JDK50D250L (1 Hose 1 Pump)
200L-300L YB65 M-40-1 380/2.8Kw 2Inch

JDK50D500L (1 Hose 1 Pump)
400L-500L YB65 M-50-1 380/3.7Kw 2.5Inch

JDK50D800L (1 Hose 1 Pump)
600L-800L YB80 M-80-1 380/5.8Kw-7Kw 3Inch

External Dimension: 1400x1300x1000(mm)

Components Installed(standard):

1. Ehad Electronic Unit
2. Flowmeter.
3. Pump.
4. Automatic Nozzle.
5. Ex-Motor

Technical Specifications:

1. Accuracy: $\pm 0.3\%$
2. Frequency: $50\text{HZ} \pm 1\text{HZ}/60\text{HZ} \pm 1\text{HZ}$
3. Delivery Rate: 25 to 250L/min
4. Rating Power: 0.75KW
5. Measurbale Minimum: 5L
6. Ambient Humidity: 30% to 90%
7. Noise: $\leq 80\text{dB(A)}$
8. Ambient Temperature: -40°C to $+60^{\circ}\text{C}$
9. Inlet Vacuum: $\geq 0.06\text{MPa}$
10. Anti-Explosive ID: Exdm[ib]ib II AT3
11. Anti-Explosive Certificate Number:
CE011154 CE011155 CE011156 CE011157
12. Totalizer Range: 0.00 to 9999999999.99
14. Range of Price: 0.01 to 99999
15. License of Manufacturing Metric Instrument: ZheZi00000625
16. Preset Min Value: 0.01 to 0.99L
17. Power Supply: $\text{AC}380\text{V} \pm 20\%$ or $\text{AC}220\text{V} \pm 20\%$