

# S- Series

## Two Nozzle

### Features:

Customer friendly operation  
Best exterior construction and good appearance.

Trustable highly precise metrology equipment.

High performance for electronic parts  
High quality explosion-proof motor with strong ability against power fluctuation  
Specially designed filtering systems with build-in re-cleanable filter

With rich functions expansion like POS for smart card and bank card

[Flexible fuel application for gasoline](#), diesel, and kerosene etc.

Works well in harsh conditions, like extremely cold, hot, humid, and sand-stormy environment

### Optional Configuration:

Printer, IC card, ID card, communication for FMS,

vapor recovery, break away, swivel, emergency stop, LED light, ect.

### Technical specifications:

Accuracy for the unit	±0.25%
Flow rate	45 - 80L/min
Ambient temperature	-25°C ~ +55°C; -40°C ~ +50°C
Relative humidity	20% - 95%
Unit noise rate	< 70dB (A);
Inlet vacuum rate for suction pump	≥ 54kPa
Communication	With RS 485 port, or current loop
Power supply	AC 220V( -15%~+10%),(50/60±1)Hz ; AC 380V( -15%~+10%); (50/60±1)Hz
Digit of sale	7digits (decimal points can be adjusted )
Digit of volume	6digits (decimal points can be adjusted )
Digit of unit price	5digits (decimal points can be adjusted )
Totalizer of sale	0-42949672.95
Totalizer of volume	0-42949672.95